

**EVO**

## Green Thermal Receipt Printer

The EVO Green Thermal Receipt Printer is one of our most efficient receipt printers. Engineered to operate day-in and day-out in the harshest of environments, the EVO Green provides the steadfast performance you need while using a fraction of the energy. Perfect for high volume retail and hospitality operations, the EVO Green features quick receipt printing, JamFree Autocutter Technology, and is backed by the best warranty in the industry.



### Key Features



#### Print Speed

220mm/sec



#### Accessories Included

Power supply and interface cables included



#### Paper Loading

Drop-in easy thermal paper loading



#### AutoCutter

JamFree AutoCutter technology



#### Multiple Interfaces

USB, Serial, Ethernet



#### Emulation

ESC/POS and OPOS compatible



#### Wall-Mountable

Convenient mounting capabilities



#### Energy Star Certified

Helps cut energy costs

#### ■ POS-X Warranty

##### Industry-leading Warranty Protection

- 3 year warranty
- \*2-day Advance Exchange - standard on all products
- Warranty extensions and overnight exchanges are available to provide means to further reduce the total cost of ownership

\*Available in USA and Canada

#### ■ POS-X Service and Support

##### 24/7 Technical Support and Lifetime Customer Support

- 24/7 access to our USA-based experienced technical support representatives
- Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products



# Green Thermal Receipt Printer

PART NUMBER		EVO-PT3-2GUS	EVO-PT3-2GUSE
INTERFACE SPECIFICATIONS			
Interfaces	USB/Serial		USB/Serial/Ethernet
Interface Details	USB 2.0/RS-232C		USB 2.0/RS-232C/(10/100)
Emulation	ESC/POS Command Compatible OPOS		
Print Method	Direct Thermal		
Printing Speed	7.87"/sec (220 mm/sec)		
Print Resolution	180 DPI x 180 DPI		
Printing Direction	Unidirectional with Friction Feed		
Sensors	Cover Open, Paper Low, Paper End		
Cash Drawer Port	1 Port, 2 Internal Circuits (24 V, 1 A max)		
Reliability	TPH Life 99.42 miles (160Km) MCBF 60,000,000 Lines		
PAPER		PHYSICAL	
Type	Thermal Paper		Dimension (WxDxH) 6.1" x 8" x 6.1" (155mm x 203mm x 155mm)
Width	1.9" (50mm) - 3.15" (80mm)		Weight 3.7 lbs (1.7 kg)
Thickness	0.002" (0.06mm) - 0.0035" (0.09mm)		Color Black
Roll Diameter	Max 3.15" (80mm)		Electrical 100–240 VAC 50/60 Hz (input) 24 VDC/1.5 A (output)
Roll Core Inner Diameter	0.492" (12.5mm) ± 0.019" (0.5mm)		
Character Set	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page) International Characters 14		ENVIRONMENTAL
Character/Line	Font A (12 x 24) 42 columns Font B (9 x 17) 56 columns		Temperature 41°F to 104°F (5°C to 40°C) operating -4°F to 140°F (-20°C to 60°C) storage
Barcodes Supported	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, PDF 417(2D)		Humidity 35% to 80% non condensing (operation) 10% to 90% non condensing (storage)
AUTO CUTTER		Warranty 3-year warranty with free *2-day Advance Exchange Service, 2-year on Autocutter and Print Head	
Type	JamFree auto-retracting guillotine		Certifications FCC, UL, CE, Energy Star, RoHs, NOM
Life	1,500,000 Cuts		Operating System WIN 95, WIN 98, WIN 2000, WIN XP, VISTA, Win 7, Win 8, OPOS drivers available
Cutting Method	Full/Partial Cut		WARRANTY EXTENSION AND UPGRADES
		ZWE-CRW	2-Year Warranty Extension
		ZOE-CRW3	*3-Year Overnight Exchange
		ZOE-CRW5	*5-Year Overnight Exchange

\*Available in USA and Canada

\*Available in USA and Canada



1975 Midway Lane, Suite O  
Bellingham, WA 98226  
sales@pos-x.com  
360.738.8433  
www.pos-x.com

DS-EVOGREENTRP REV 0116

