

EVO

TP4 TruFlat POS Terminal

The EVO TP4 TruFlat sets a whole new standard by offering enterprise-class build quality, P-CAP touchscreen technologies, and the latest in high-performance Intel® processors. Available with Celeron™, Pentium™, Core i3™, Core i5™, and Core i7™ processors, the EVO TP4 thrives in the most demanding environments. The EVO TP4 has an IP54 certified rating for both dust and splash resistance.



Shown with optional MSR



Shown with optional customer display



Key Features



Baytrail and Haswell Processors

Available with Intel Celeron, Pentium, Core i3, Core i5, or Core i7



Touchscreen

15" (381mm) zero bezel, projected capacitive touchscreen technology



Hard Drive

2.5" (64mm) 500GB HDD or 60-120GB SSD



Built In Cable Management

Keeps cords out of sight



EZHD Slot

Makes for quick HDD or SSD replacement



IP54 Rating

Resistant to dust buildup and splashing water



Aluminum Alloy Frame

Provides bump-free operation



Optional Accessories

Optional integrated MSR, VFD customer display, 8.4" (213mm) rear LCD display, 15" (381mm) rear LCD display, or Biometric Reader

■ POS-X Warranty

Industry-leading Warranty Protection

- 3 year warranty
- *2-day Advance Exchange - standard on all products
- Warranty extensions and overnight exchanges are available to further reduce the total cost of ownership

*Available in USA and Canada

■ POS-X Service and Support

24/7 Technical Support and Lifetime Customer Support

- 24/7 access to our USA-based experienced technical support representatives
- Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products

MODELS	EVO-TP4D-F	EVO-TP4D-G	EVO-TP4D-H	EVO-TP4D-J	EVO-TP4D-K	EVO-TP4D-L
Processor	Intel® Celeron J1900 2.4GHz Quad Core*	Intel® Celeron G1820 2.7GHz Dual Core*	Intel® Pentium G3420 3.2GHz Dual Core*	Intel® Core i3- 4330 3.5GHz Dual Core*	Intel® Core i5- 4570S 3.6GHz Quad Core*	Intel® Core i7- 4770S 3.9GHz Quad Core*
Chip Set	Processor Integrated	Intel Lynx Point PCH H81				
System Memory	1 x DDR3L 2GB to 8GB	1 x DDR3 DIMM 4GB to 8GB				
Hard Drive	500GB HDD or 60-120GB SSD					
Graphic Memory	Intel Gen7 up to 854MHz	Intel® HD Graphic DX11.1				
GigaLAN (10/100/1000)	1 x RJ45					
Weight (w/base)	15 lbs (6.8kg)	15.4 lbs (7kg)				
Electrical	65W/19V	120W/19V				
PORTS	EVO-TP4D-F	EVO-TP4D-G	EVO-TP4D-H	EVO-TP4D-J	EVO-TP4D-K	EVO-TP4D-L
Parallel	1					
USB	5 x USB Type A (USB 3.0 / 2.0 x1, USB 2.0 x4)	6 x USB Type A (USB 3.0 / 2.0 x2, USB 2.0 x4)				
Serial	3 x RJ45 COM3 with 5V/12V	3 x RJ45 COM3 with 5V/12V, 1 DB9				
VGA	1					
Cash Drawer Port	1					
Speakers	2					
PHYSICAL		ENVIRONMENTAL				
Housing	Die Cast Aluminum	Ingress Protection Rating IP54-Resistant to dust buildup and splashing water				
Dimensions (w/base) (WxDxH)	14.21" x 9.76" x 13.27" (361mm x 248mm x 337mm)	Operating Temperature 32°F to 95°F (0°C to 35°C)				
VESA Wall Mountable	3.9" x 3.9" (100mm x 100mm)	Humidity 20% to 80% non-condensing				
Tilt Angle	0° – 90°	Warranty 3-year warranty with free *2-day Advance Exchange Service				
Housing Color	Black	Certifications FCC, Class A, CE, LVD, RoHs, NOM				
Bezel	TruFlat Zero Bezel	Supported OS POS Ready 2009 & 7/Win 7 Pro/Available with no O/S				
LCD Display	15" (381mm) LED LCD	OPTIONAL ACCESSORIES				
Touch Technology	Projected Capacitive (P-CAP)	EVO-MR4 3 Track Magnetic Stripe Reader with USB interface				
WARRANTY EXTENSION AND UPGRADES		EVO-BR4 Integrated U.are.U 4500 bio fingerprint reader				
ZWE-TPC	2-Year Warranty Extension	EVO-RD4-VFD Integrated 2x20 VFD Customer Display				
ZOE-TPC3	3-Year Overnight Exchange**	EVO-RD4-LCD8 Integrated Rear Display, 8.4" (213mm) LCD w/VGA Cable & Mount				
ZOE-TPC5	5-Year Overnight Exchange**	EVO-RD4-LCD15 Integrated Rear Display, 15" (381mm) LCD w/VGA Cable and Mount				
		EVO-XZ4-M100 Universal VESA Mount for All Terminals and Touch Monitors				

*Shipped product may include an equivalent or faster processor. Processor speeds based on Passmmark® benchmark scores. Speeds shown are maximum burst speed.

**Available in USA and Canada.

POSX

POINT OF SALE SIMPLIFIED

*Shipped product may include an equivalent or faster processor. Processor speeds based on Passmark® benchmark scores. Speeds shown are maximum burst speed.
**Available in USA and Canada.



1975 Midway Lane, Suite O
Bellingham, WA 98226
sales@pos-x.com
360.738.8433
www.pos-x.com