

Linear Wireless Barcode Scanner

The ION Linear Wireless is part of the costeffective, high performance POS-X ION Series. The ION Linear Wireless is equipped with wireless technology that has lower interference rates, and uses less energy than other wireless technologies; therefore, the barcode scanner has a longer battery life between charges. The ION Linear Wireless incorporates a convenient USB dongle for a clean wireless connection, a sleek, shatterresistant ergonomic housing, and an industryleading warranty and support package, which comes standard with every POS-X product.





Key Features



Decode Capabilities

Reads all standard linear 1D barcodes



Scan Rate Reads up to 270 scans/second

Reading Distance

From 1.2" to 18.1" (30mm to 460mm)



Receiver Compact USB dongle



Wireless Technology Up to 328 feet



Operating Time Approximately 70,000 scans/charge

POS-X Warranty

Industry-leading Warranty Protection

- 3 year warranty
- *2-day Advance Exchange standard on all products
- · Warranty extensions and overnight exchanges are available to provide means to further reduce the total cost of ownership

*Available in USA and Canada

POS-X Service and Support

24/7 Technical Support and Lifetime Customer Support 24/7 access to our USA-based experienced technical support representatives

- · Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products

HOU

Linear Wireless Barcode Scanner

PERFORMANCE	
Light Source	630 nm ±20 nm CCD
Visual Indicators	Blue LED: decoding successful
System Interface	USB
Depth of Field	1.2" to 18.1" (30.5mm to 460mm)
Resolution	4 mil (0.1mm)
Scanning Angle	65°
Scan Rate	270 scans per second
Print Contrast	Minumum 45% contrast
Light Levels	3000 LUX-8000 LUX
FEATURES	
Decode Capabilities	Reads all standard 1D symbologies
Programmable Features	Prefix Code, Length Code, Barcode Type, ISBN/ISSN/CLSI/ UK Plessey Conversion, Scanning Mode, Time Out, Baud Rate
WIRELESS TECHNOLOGY	
Radio Frequency	2.4GHz–2.5GHz
Range	Up to 328 ft. (100m) line of sight
PHYSICAL	
Weight	.22 lb (180g) w/cable
Housing	ABS
Dimensions (LxWxH)	7.3" x 2.6" x 3.6" (186mm x 67mm x 91mm)
Color	Black

ELECTRICAL		
Power Input	5 VDC ± 5% (scanner) 5 VDC ± 5% (dongle)	
Current	70mA	
BATTERY		
Battery Type	Rechargeable Polymer	
Battery Capacity	1200mAh	
Recharge Time	4 to 5 hours via 5V USB	
Operating Time	Approximately 70,000 scans/charge	
ENVIRONMENTAL		
Temperature	32°F to 104°F (0°C to 40°C) (operating) 68°F to 149°F (20°C to 65°C) (storage)	
Humidity	5% to 95% relative humidity, non-condensing	
Shock Resistance	Withstands multiple drops from 3.9' (1.2m)	
Warranty	3-year warranty with free *2-day Advance Exchange Service, 1-year warranty on battery	
Certifications	CE, UL, SELV, CSA, FCC Class-A, ROHS, NOM	
OPTIONAL ACCESSORIES		
ION-SP1-ASTAND	ION Barcode Scanner stand	
WARRANTY EXTENSION AND UPGRADES		
ZWE-BMP	2-Year Warranty Extension	
ZOE-BMP3	*3-Year Overnight Extension	
ZOE-BMP5	*5-Year Overnight Extension	

*Available in USA and Canada



1975 Midway Lane, Suite O Bellingham, WA 98226 sales@pos-x.com 360.738.8433 www.pos-x.com

