

## XP8200

## Customer Pole Display

The XP8200 Pole Display was designed to blend in beautifully with your POS station. The lack of dip switches make configuration through the provided software a breeze. Featuring OPOS support and several popular emulations, including Epson, CD-5220, and UTC. The XP8200 makes a great addition to any POS station with larger than industry average characters and features an adjustable height stand.



Shown with Medium Display



## Key Features



### Display

Ideal 2-line, 20 character/line Vertical Display for smaller counter spaces



### Adjustable Height

Adjustable height and pitch angles



### Emulation

10 standard display emulations in addition to OPOS



### Multiple Interfaces

USB and RS232 Interfaces

## ■ POS-X Warranty

### Industry-leading Warranty Protection

- 3 year warranty
- \*2-day Advance Exchange - standard on all products
- Warranty extensions and overnight exchanges are available to provide means to further reduce the total cost of ownership

\*Available in USA and Canada

## ■ POS-X Service and Support

### 24/7 Technical Support and Lifetime Customer Support

- 24/7 access to our USA-based experienced technical support representatives
- Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products

## PERFORMANCE

Type	Vacuum Fluorecent Display
Display Pattern	5 x 7 dot matrix
System Interface	USB, RS-232 (dB9)
Brightness	300 - 700 nits
Character Type	95 Alphanumeric and 32 International
Character Size (W x H)	0.207" x 0.366" (5.3mm x 9.3mm)
Character Number	20 per row x 2 rows
Emulations	EPSON ESC/POS, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL, LD-220

## PHYSICAL

Weight	2.3 lbs (1kg)
Dimensions Panel (Wx-DxH)	8.7" x 2" x 3.4" (221mm x 51mm x 86mm)
Dimensions Base (Wx-DxH)	8.5" x 4.2" x 1.4" (216mm x 107mm x 36mm)
Extensions	2" x 5.1" (51mm x 130mm)
Viewing Angle	Maximum 90°
Pitch Angle	Maximum 30°
Horizontal Rotation	Maximum 360°
Interface Cable Lenth	5' (1.7m)
Color	Black

## ELECTRICAL

Power	5V, 1A
-------	--------




## ENVIRONMENTAL

Temperature	32°F to 114°F (0°C to 45.6°C) operating
Humidity	10% to 95% non-condensing
Shock Resistance	Withstands multiple drops from 3.3' (1m)

## WARRANTY EXTENSIONS

ZWE-CRW	2-Year Warranty Extension
ZOE-CRW3	*3-Year Overnight Exchange
ZOE-CRW5	*5-Year Overnight Exchange

\*Available in USA and Canada



1975 Midway Lane, Suite O  
Bellingham, WA 98226  
sales@pos-x.com  
360.738.8433  
www.pos-x.com

DS-XP8200 REV 0915

